

# CSE 3318-003/004 Lab Assignment 1

Due September 15

## Goal:

Understanding of sorting concepts.

## Requirements:

1. Write a C program to take a sequence of  $n$  integer values and remove duplicate occurrences, i.e. only the first occurrence of each value will remain.  $n$  will be the first input value and the sequence may be read using `scanf ( )`s. The phases for performing this task are:
  - a. Read input sequence of values, each value giving an ordered pair (value, position indicator).
  - b. Sort the pairs in ascending order by value in a stable fashion. If your chosen sort is stable, then the key is just the value. If your chosen sort is unstable, the key must be extended with the position indicator.
  - c. Using one pass ( $\Theta(n)$  time) over the sorted result, remove any occurrences beyond the first one for a key.
  - d. Sort the pairs using the (unique) position indicator as the key.
  - e. Output the number of unique values followed by the values (without the position indicators).

The input will be read from standard input (`stdin`) as either keyboard typing or as a shell redirect (`<`) from a file. Prompts/menus are completely unnecessary!

2. Submit your program on Canvas by 5:00 p.m. on Tuesday, September 15. One of the comment lines should indicate the compilation command used on OMEGA.

## Getting Started:

1. You may use any sort you wish, but the standard library `qsort ( )` is recommended.
2. Processing for the input:

Input:	a. Array of pairs	b. After sorting	c. Remove extras	d. After sorting	e. Output:
10	0: 3 0	0: 1 5	0: 1 5	0: 3 0	7
3	1: 3 1	1: 2 4	1: 2 4	1: 7 2	3
3	2: 7 2	2: 2 8	2: 3 0	2: 5 3	7
7	3: 5 3	3: 3 0	3: 4 6	3: 2 4	5
5	4: 2 4	4: 3 1	4: 5 3	4: 1 5	2
2	5: 1 5	5: 3 7	5: 7 2	5: 4 6	1
1	6: 4 6	6: 4 6	6: 9 9	6: 9 9	4
4	7: 3 7	7: 5 3			9
3	8: 2 8	8: 7 2			
2	9: 9 9	9: 9 9			
9					